

Software to Download:

Cytoscape

<https://cytoscape.org>

BGGN 213

Biological Network Analysis


Lecture 17

Barry Grant
UC San Diego

<http://thegrantlab.org/bggcn213>

R 'Knowledge Check' Quiz Results


Winter 2020



Frequently Missed Questions

What is the minimum input required to produce a single-layer scatter plot


2 / 22 correct responses



Frequently Missed Questions

If I have a data frame "df" with 2 rows and 5 columns, what will `df[,1]` return?

4 / 22 correct responses




2 of 6

Frequently Missed Questions

Select the correct way(s) to extract a vector from a row in the data frame X. The name of the first row is month.

9 / 22 correct responses




3 of 6

Frequently Missed Questions

`jal <- function(x) {y=x^2; return(y)}` #If I want to execute `jal(hmk)`, what kind of data type can `hmk` be without `r...n` error message? Check all that apply

5 / 22 correct responses




4 of 6

Frequently Missed Questions

The working directory is in the "r_projects" folder, and it contains the file `m_data.csv`. Select the correct way(s) to read `m_data` into X.

4 / 22 correct responses




5 of 6

Frequently Missed Questions


The "r_dat" folder is not in your working directory but it is in your home directory. It contains the file k_table.csv. Correct way(s) to read k_table.csv into Y.

15 / 22 correct responses



6 of 6


Information in the **file system** is stored in files, which are stored in **directories** (a.k.a. folders). Directories can also store other directories, which forms a **directory tree**.











The forward slash character '/' is used to represent the **root** directory of the whole file system, and is also used to separate directory names. E.g. **/Users/barry/Desktop/myfile.csv**



UNIX Basics: Using the filesystem

| | |
|--------------|--|
| ls | List files and directories |
| cd | Change directory (i.e. move to a different 'folder') |
| pwd | Print working directory (which folder are you in) |
| mkdir | MaKe a new DIRectories |
| cp | CoPy a file or directory to somewhere else |
| mv | MoVe a file or directory (basically rename) |
| rm | ReMove a file or directory |









Side Note: File Paths

- An **absolute path** specifies a location from the root of the file system. E.g. `/Users/barry/Downloads/data.csv`
`~/Downloads/data.csv`
- A **relative path** specifies a location starting from the current location. E.g. `../data.csv`

| | |
|-------|--|
| . | Single dot '.' (for current directory) |
| .. | Double dot '..' (for parent directory, back one dir in our tree) |
| ~ | Tilda '~' (shortcut for your home directory) |
| [Tab] | Pressing the tab key can autocomplete names |

TODAYS MENU:

- Network introduction
- Network visualization
- Network analysis
- Hands-on:
Cytoscape and R (igraph) software tools for network visualization and analysis

TODAYS MENU:

► Network introduction


► Network visualization

► Network analysis

► Hands-on:


Cytoscape and R (igraph) software tools for network visualization and analysis

Networks can be used to model many types of biological data




Biological Networks

- **Represent biological interactions**
 - Physical, regulatory, genetic, functional, etc.
- **Useful for discovering relationships in big data**
 - Better than tables in Excel
- **Visualize multiple heterogenous data types together**
 - Help highlight and see interesting patterns
- **Network analysis**
 - Well established quantitative metrics from graph theory




Pathways vs Networks

EGFR-centered
Pathway



- Detailed, high-confidence consensus
- Biochemical reactions
- Small-scale, fewer genes
- Concentrated from decades of literature

EGFR-centered
Network



- Simplified cellular logic, noisy
- Abstractions: directed, undirected
- Large-scale, genome-wide
- Constructed from *omics* data integration

Goal


1 Enrichment of fixed gene sets

Identification of pre-built pathways or networks that are enriched in a set of mutated or differentially expressed genes

2 De novo sub-network construction and clustering

Construction of specific sub-networks from the set of mutated or differentially expressed genes to identify an extended list of putative cancer genes

Output



Goal


1 Enrichment of fixed gene sets

Identification of pre-built pathways or networks that are enriched in a set of mutated or differentially expressed genes

2 De novo sub-network construction and clustering

Construction of specific sub-networks from the set of mutated or differentially expressed genes to identify an extended list of putative cancer genes

Output



What biological process is altered in this cancer?

Are NEW pathways altered in this cancer? Are there clinically relevant tumor subtypes?

Network analysis is complementary to pathway analysis and can be used to show how key components of different pathways interact.

This can be useful for identifying regulatory events that influence multiple biological processes and pathways

Network analysis approaches






Image from: van Dam et al. (2017) <https://doi.org/10.1093/bib/bbw139>


Applications of Network Biology




jActiveModules, UCSD



PathBlast, UCSD



MCODE, University of Toronto



DomainGraph, Max Planck Institute

Slide from: humangenetics-amc.nl

- **Gene Function Prediction** – shows connections to sets of genes/proteins involved in same biological process
- **Detection of protein complexes/other modular structures** – discover modularity & higher order organization (motifs, feedback loops)
- **Network evolution** – biological process(es) conservation across species
- **Prediction of new interactions and functional associations** – Statistically significant domain-domain correlations in protein interaction network to predict protein-protein or genetic interaction; allostery in molecular networks

What's missing

- **Dynamics**
 - Pathways/networks represented as static processes
 - Difficult to represent a calcium wave or a feedback loop
 - More detailed mathematical representations exist that handle these e.g. Stoichiometric modeling, Kinetic modeling (VirtualCell, E-cell, ...)
- **Detail** – atomic structures & exclusivity of interactions.
- **Context** – cell type, developmental stage

What have we learned so far...

- **Networks are useful for seeing relationships in large data sets**
 - Important to understand what the nodes and edges mean
 - Important to define the biological question - know what you want to do with your gene list or network
- **Many methods available for network analysis**
 - Good to determine your question and search for a solution
 - Or get to know many methods and see how they can be applied to your data

TODAYS MENU:

► Network introduction

► Network visualization

► Network analysis

► Hands-on:

Cytoscape and R (igraph) software tools for network visualization and analysis

Network Visualization Outline


- Network representations
- Automatic network layout
- Visual features
- Visually interpreting a network

Network representations

| Relationships | Optional weight |
|---------------|-----------------|
| A1 ↔ A2 | 1 |
| A1 ↔ A3 | 3 |
| A2 ↔ A3 | 1 |
| A2 ↔ A4 | 2 |
| A2 ↔ A5 | 1 |
| A3 ↔ A4 | 1 |
| A3 ↔ A5 | 1 |
| A3 ↔ A7 | 1 |
| A5 ↔ A4 | 1 |
| A5 ↔ A6 | 1 |
| A6 ↔ A8 | 1 |
| A6 ↔ A9 | 2 |
| A8 ↔ A9 | 3 |


1

List of relationships



2

Network view




3


Adjacency matrix view

Network view is most useful when network is sparse!

Automatic network layout



- Modern **graph layouts** are optimized for speed and aesthetics. In particular, they seek to minimize overlaps and edge crossing, and ensure similar edge length across the graph.




Force-directed layout:

Nodes repel and edges pull


- Good for up to 500 nodes
 - Bigger networks give hairballs
 - Reduce number of edges
 - Or just use a heatmap for dense networks
- Advice: try force directed first, or hierarchical for tree-like networks
- Tips for better looking networks
 - Manually adjust layout
 - Load network into a drawing program (e.g. Illustrator) and adjust labels

Dealing with 'hairballs': zoom or filter




Visual Features

- Node and edge attributes
 - Text (string), integer, float, Boolean, list
 - E.g. represent gene, interaction attributes
- Visual attributes
 - Node, edge visual properties
 - Color, shape, size, borders, opacity...



Visually Interpreting a Network



What to look for:
Data relationships
Guilt-by-association
Dense clusters
Global relationships

What have we learned so far...

- Automatic layout is required to visualize networks
- Networks help you visualize interesting relationships in your data
- Avoid hairballs by focusing analysis
- Visual attributes enable multiple types of data to be shown at once – useful to see their relationships

TODAYS MENU:

- Network introduction
- Network visualization
- **Network analysis**
- **Hands-on:**
 - Cytoscape and R (igraph) software tools for network visualization and analysis

Hands-on: Part 1

https://bioboot.github.io/bgg213_W20/lectures/#17


- The data used in **part 1** is from yeast, and the genes **Gal1**, **Gal4**, and **Gal80** are all yeast transcription factors. The experiments all involve some perturbation of these transcription factor genes.

Hands-On: Lab 1

Practical issues

Lab1

- Major tools for the **creation, manipulation and visualization** of biological networks include:
 - Cytoscape,
 - Gephi
 - R packages (igraph, graph, tidygraph, ggraph)
- Tools for network analysis and modeling include:
 - Cytoscape apps/plugins
 - R packages (igraph and many others)
 - NetworkX (for Python)
 - ByoDyn, COPASI



Cytoscape Memory Issues

- Cytoscape uses lots of memory and doesn't like to let go of it
 - An occasional restart when working with large networks is a good thing
 - Destroy views when you don't need them
- Since version 2.7, Cytoscape does a much better job at "guessing" good default memory sizes than previous versions but it still not great!
 - Java doesn't give us a good way to get the memory right at start time

Cytoscape Sessions

- Sessions save pretty much everything:
 - Networks
 - Properties
 - Visual styles
 - Screen sizes
- Saving a session on a large screen may require some resizing when opened on your laptop

TODAYS MENU:

▸ Network introduction

▸ Network visualization

▸ **Network analysis**


▸ **Hands-on:**

- Cytoscape and R (igraph) software tools for network visualization and analysis

Introduction to graph theory

- Biological network analysis historically originated from the tools and concepts of **social network analysis** and the application of **graph theory** to the social sciences.
- Wikipedia defines graph theory as:
 - ▀ “[...] the study of graphs used to model pairwise relations between objects. A graph in this context is made up of **vertices** connected by **edges**”.
- In practical terms, it is the set of concepts and methods that can be used to visualize and analyze networks

Network or graph



Node or vertex: protein, gene, drug, disease

Edge or link: relation between nodes

- Binary or continuous
- Directed or undirected
- Edge types

Types of network edges

Undirected



Connection, without a given 'flow' implied

(e.g. protein A binds protein B)


Directed



There is directional flow/signal implied

(e.g. metabolic or gene networks)


Weighted



Edges can also have weight

(i.e. a 'strength' of interaction).

- Every network can be expressed mathematically in the form of an adjacency matrix




Network topology

- Topology is the way in which the nodes and edges are arranged within a network.
- The most used topological properties and concepts include:
 - Degree** (i.e. how many node neighbors)
 - Communities** (i.e. clusters of well connected nodes)
 - Shortest Paths** (i.e. shortest distance between 2 nodes)
 - Centralities** (i.e. how 'central' is a given node?)
 - Betweenness** (a measure of centrality based on shortest paths)



Degree $k_i = \text{number of links connected to node } i$




Distance $d_{ij} = \text{shortest path length between node } i \text{ and } j$




Betweenness $b_i = \sum_{j,k} p_{ij}(l) p_{kj}(l) / p_{jk}$ p_{ij} : number of shortest paths between i and j
 $p_{ij}(l)$: number of shortest paths between i and j going through node l

Network Measures: Degree

a Undirected network





b Directed network



Degree Distribution

A Random network

B Scale-free network





$P(k)$ is probability of each degree k , i.e. fraction of nodes having that degree.

For random networks, $P(k)$ is normally distributed.


For real networks the distribution is often a power-law:

$$P(k) \sim k^{-\gamma}$$

Such networks are said to be **scale-free**



Random graphs vs scale free




Scale-Free Networks are Robust

- Complex systems (cell, internet, social networks), are resilient to component failure
- Network topology plays an important role in this robustness
 - Even if ~80% of nodes fail, the remaining ~20% still maintain network connectivity
- **Attack vulnerability** if hubs are selectively targeted
- In yeast, only ~20% of proteins are lethal when deleted, and are 5 times more likely to have degree $k > 15$ than $k < 5$.

Implications

- Many biological networks (protein-protein interaction networks regulatory networks, etc...) are thought to have hubs, or nodes with high degree.
- For protein-protein interaction networks (PPIs) these hubs have been shown to be older [1] and more essential than random proteins [2]
 - [1] Fraser et al. *Science* (2002) 296:750
 - [2] Jeoung et al. *Nature* (2001) 411:41


Analyzing the topological features of a network is a useful way of identifying relevant participants and substructures that may be of biological significance.



Centrality analysis


- Centrality gives an estimation on how important a node or edge is for the connectivity or the information flow of the network
- It is a useful parameter in signalling networks and it is often used when trying to find drug targets.
- Centrality analysis in PPINs usually aims to answer the following question:
 - ➡ Which protein is the most important and why?

Bigger, redder nodes have higher **centrality values** in this representation.



Betweenness centrality


- Nodes with a high betweenness centrality are interesting because they lie on communication paths and can control information flow.
- The number of shortest paths in the graph that pass through the node divided by the total number of shortest paths.
- Betweenness centrality measures how often a node occurs on all shortest paths between two nodes.



Community analysis

- **Community:** A general, catch-all term that can be defined as a group (i.e. *cluster*) of nodes that are more connected within themselves than with the rest of the network. The precise definition for a community will depend on the method or algorithm used to define it.

Looking for communities in a network is a nice strategy for reducing network complexity and extracting functional modules (e.g. protein complexes) that reflect the biology of the network.



TODAYS MENU:

- Network introduction
- Network visualization
- Network analysis

▸ Hands-on:

- Cytoscape and R (igraph) software tools for network visualization and analysis

Hands-on: Part 2

https://bioboot.github.io/bgg213_W20/lectures/#17

- The data used in **part 2** is from an ocean metagenomic sequencing project - where all the genetic material in a sample of ocean water is sequenced.
- We will use the R package **igraph** and the bioconductor package **RCy3** together with Cytoscape.
- Many of these microbial species in these types of studies have not yet been characterized in the lab.
 - Thus, to know more about the organisms and their interactions, we can observe which ones occur at the same sites.
 - One way to do that is by using **co-occurrence networks** where you examine which organisms occur together at which sites.

Hands-On: Lab2

Practical issues

Hands-On: Lab2

- Major tools for the **creation, manipulation** and **visualization** of biological networks include:
 - Cytoscape,
 - Gephi
 - R packages (igraph, graph, tidygraph, ggraph)



Lab2

- Tools for network analysis and modeling include:
 - Cytoscape apps/plugins
 - R packages (igraph and many others)
 - NetworkX (for Python)
 - ByoDyn, COPASI

Our Input

| Relationships | Optional weight |
|---------------|-----------------|
| A1 ↔ A2 | 1 |
| A1 ↔ A3 | 3 |
| A2 ↔ A3 | 1 |
| A2 ↔ A4 | 2 |
| A2 ↔ A5 | 1 |
| A3 ↔ A4 | 1 |
| A3 ↔ A5 | 1 |
| A3 ↔ A7 | 1 |
| A5 ↔ A4 | 1 |
| A5 ↔ A6 | 1 |
| A6 ↔ A8 | 1 |
| A6 ↔ A9 | 2 |
| A8 ↔ A9 | 3 |

Our Output



1

List of relationships

2

Network view

3

Adjacency matrix view

Network view is most useful when network is sparse!

Summary

- Network biology makes use of **graph theory** to represent and analyze complex biological systems as a set of **nodes** and **edges**.
- Major types of biological networks include: genetic, metabolic, cell signaling etc.
- Biological networks have a number of characteristics, mainly:
 - Scale-free**: A small number of nodes (**hubs**) are a lot more connected than the average node.
 - Transitivity**: The networks contain **communities** of nodes that are more connected internally than they are to the rest of the network.
- Two of the most used topological methods are:
 - Centrality analysis**: Which identifies the most important nodes in a network, using different ways to calculate centrality.
 - Community detection**: Which aims to find heavily inter-connected components that may represent e.g. protein complexes and machineries

Summary cont...

- Cytoscape** is very useful for network visualization and:
 - Provides basic network manipulation features
 - Plugins/Apps are available to extend analysis functionality
- The R **igraph** package has extensive network analysis functionality beyond that in Cytoscape
- The R bioconductor **RCy3** package allows us to bring networks and associated data from R to Cytoscape so we can have the best of both worlds.
- Other popular tools include Gephi and NetworkX

Network Analysis Overview

