



BIMM 143

Data visualization with R

Lecture 5

Barry Grant
UC San Diego

<http://thegrantlab.org/bimm143>

Recap From Last Time:

- What is R and why should we use it?
- Familiarity with R's basic syntax.
- Familiarity with major R data structures namely **vectors** and **data.frames**.
- Understand the basics of using **functions** (arguments, vectorization and re-cycling).
- Appreciate how you can use R scripts to aid with reproducibility.

[\[MPA Link\]](#)

Today's Learning Goals

- Appreciate the major elements of **exploratory data analysis** and why it is important to visualize data.
- Be conversant with **data visualization best practices** and understand how good visualizations optimize for the human visual system.
- Be able to generate informative graphical displays including **scatterplots, histograms, bar graphs, boxplots, dendrograms** and **heatmaps** and thereby gain exposure to the extensive graphical capabilities of R.
- Appreciate that you can build even more complex charts with **ggplot** and additional R packages such as **rgl**.


Today's Learning Goals


- Appreciate the major elements of **exploratory data analysis** and why it is important to visualize data.
- Be conversant with **data visualization best practices** and understand how good visualizations optimize for the human visual system.
- Be able to generate informative graphical displays including **scatterplots, histograms, bar graphs, boxplots, dendrograms** and **heatmaps** and thereby gain exposure to the extensive graphical capabilities of R.
- Appreciate that you can build even more complex charts with **ggplot** and additional R packages such as **rgl**.

Why visualize at all?


	x	y
1	5.00	0.00
2	4.18	2.75
3	1.98	4.59
4	-0.86	4.92
5	-3.43	3.64
6	-4.86	1.16
7	-4.70	-1.70
8	-2.99	-4.01
9	-0.30	-4.99
10	2.49	-4.34
11	4.46	-2.25
12	4.97	0.57
13	3.84	3.20
14	1.45	4.79
15	-1.42	4.79

	x	y
Min.	-4.86	-4.99
1st Qu.	-2.21	-1.98
Median	1.45	1.16
Mean	0.65	0.87
3rd Qu.	4.01	4.12
Max.	5.00	4.92





https://bioboot.github.io/bimm143_F18/class-material/05_draw_circle_points/





Exploratory Data Analysis

- ALWAYS look at your data!
- If you can't see it, then don't believe it!
- Exploratory Data Analysis (EDA) allows us to:
 1. Visualize distributions and relationships
 2. Detect errors
 3. Assess assumptions for confirmatory analysis
- EDA is the first step of data analysis!


Exploratory Data Analysis 1977

- Based on insights developed at Bell Labs in the 60's
- Techniques for visualizing and summarizing data
- What can the data tell us? (in contrast to “confirmatory” data analysis)
- Introduced many basic techniques:
 - 5-number summary, box plots, stem and leaf diagrams,...
- 5 Number summary:
 - extremes (min and max)
 - median & quartiles
 - More robust to skewed & longtailed distributions



Side-note: **boxplots**

- **Box-and-whisker plot** : a graphical form of 5-number summary (Tukey)



```
boxplot( rnorm(1000,0) )
```

```
summary(); hist()
```


The Trouble with Summary Stats





Set A		Set B		Set C		Set D	
X	Y	X	Y	X	Y	X	Y
10	8.04	10	9.14	10	7.46	8	6.58
8	6.95	8	8.14	8	6.77	8	5.76
13	7.58	13	8.74	13	12.74	8	7.71
9	8.81	9	8.77	9	7.11	8	8.84
11	8.33	11	9.26	11	7.81	8	8.47
14	9.96	14	8.1	14	8.84	8	7.04
6	7.24	6	6.13	6	6.08	8	5.25
4	4.26	4	3.1	4	5.39	19	12.5
12	10.84	12	9.11	12	8.15	8	5.56
7	4.82	7	7.26	7	6.42	8	7.91
5	5.68	5	4.74	5	5.73	8	6.89


Summary Statistics Linear Regression

$$\begin{aligned} \mu_X &= 9.0 & \sigma_X &= 3.317 & Y &= 3 + 0.5 X \\ \mu_Y &= 7.5 & \sigma_Y &= 2.03 & R^2 &= 0.67 \end{aligned}$$

[Anscombe 73]

Looking at Data






```
X Mean: 54.2659224  
Y Mean: 47.8313999  
X SD   : 16.7649829  
Y SD   : 26.9342120  
Corr.  : -0.0642526
```

Key point: You need to visualize your data!

<https://github.com/stephlocke/datasauRus>

Today's Learning Goals


- Appreciate the major elements of **exploratory data analysis** and why it is important to visualize data.
- Be conversant with **data visualization best practices** and understand how good visualizations optimize for the human visual system.
- Be able to generate informative graphical displays including **scatterplots, histograms, bar graphs, boxplots, dendrograms** and **heatmaps** and thereby gain exposure to the extensive graphical capabilities of R.
- Appreciate that you can build even more complex charts with **ggplot** and additional R packages such as **rgl**.



The Elements of Graphing Data

William S. Cleveland





The Visual Display
of Quantitative Information

EDWARD R. TUFTE


Key Point:

Good visualizations optimize for the human visual system.

Key Point: The most important measurement should exploit the highest ranked encoding possible


- Position along a common scale
- Position on identical but nonaligned scales
- Length
- Angle or Slope
- Area
- Volume or Density or Color saturation/hue

Key Point: The most important measurement should exploit the highest ranked encoding possible



- Position along a common scale
- Position on identical but nonaligned scales
- Length
- Angle or Slope
- Area
- Volume or Density or Color saturation/hue

Key Point: The most important measurement should exploit the highest ranked encoding possible



- Position along a common scale
- Position on identical but nonaligned scales
- Length
- Angle or Slope
- Area

- Volume or Density or **Color saturation/hue**

luminance





saturation




hue















Observation: Alphabetical is almost never the correct ordering of a categorical variable.









If we did not have the legend would you know which was low or high mpg?




The most important measurement should exploit the highest ranked encoding possible.

- Position along a common scale
- Position on identical but nonaligned scales
- Length
- Angle or Slope
- **Area**
- Volume or Density or Color saturation/hue







The most important measurement should exploit the highest ranked encoding possible.

- Position along a common scale
- Position on identical but nonaligned scales
- Length
- Angle or **Slope**
- Area
- Volume or Density or Color saturation/hue

Cadillac Fleet

Lincoln Continental

Camaro Z28

Duster 360

Chrysler Imperial

Maserati Bor

AMC Javelin

Merc 450SLC

Dodge Challenger

Ford Pantera

Merc 450SE

Merc 450SL

Merc 280C

Valiant

Hornet Sport

Merc 280

Pontiac Firebird

Ferrari Dino

Mazda RX4

Mazda RX4

Hornet 4 Drive

Volvo 142E

Toyota Corolla

Datsun 710

Merc 230

Merc 240D

Porsche 914

Fiat X1-9

Honda Civic

Lotus Europa

Fiat 128

Toyota Corolla

Cadillac Fleet

Lincoln Continental

Camaro Z28

Duster 360

Chrysler Imperial

Maserati Bor

AMC Javelin

Merc 450SLC

Dodge Challenger

Ford Pantera

Merc 450SE

Merc 450SL

Merc 280C

Valiant

Hornet Sport

Merc 280

Pontiac Firebird

Ferrari Dino

Mazda RX4

Mazda RX4

Hornet 4 Drive

Volvo 142E

Toyota Corolla

Datsun 710

Merc 230

Merc 240D

Porsche 914

Fiat X1-9


Honda Civic

Lotus Europa


Fiat 128

Toyota Corolla





If growth (slope) is important, plot it directly.



The most important measurement should exploit the highest ranked encoding possible.

- Position along a common scale
- Position on identical but nonaligned scales
- Length
- **Angle** or Slope
- Area
- Volume or Density or Color saturation/hue

Observation: Pie charts
are ALWAYS a mistake.

Apart from MPAs :-)

Piecharts are the information visualization equivalent of a roofing hammer to the frontal lobe. They have no place in the world of grownups, and occupy the same semiotic space as short pants, a runny nose, and chocolate smeared on one's face. They are as professional as a pair of assless chaps.

<http://blog.codahale.com/2006/04/29/google-analytics-the-goggles-they-do-nothing/>


Piecharts are the information visualization equivalent of a roofing hammer to the frontal lobe. They have no place in the world of grownups, and occupy the same semiotic space as short pants, a runny nose, and chocolate smeared on one's face. **They are as professional as a pair of assless chaps.**

<http://blog.codahale.com/2006/04/29/google-analytics-the-goggles-they-do-nothing/>

Who do you think did a better job in tonight's debate?

Among Republicans

Among Democrats




 Share

POLITICO

Who do you think did a better job in tonight's debate?

Among Republicans

Among Democrats



 Share

POLITICO

Tables are preferable to graphics for many small data sets. A table is nearly always better than a dumb pie chart; the only thing worse than a pie chart is several of them, for then the viewer is asked to compare quantities located in spatial disarray both within and between pies... Given their low data-density and failure to order numbers along a visual dimension, **pie charts should never be used.**


-Edward Tufte, The Visual Display of Quantitative Information

Tables are preferable to graphics for many small data sets. A table is nearly always better than a dumb pie chart; the only thing worse than a pie chart is several of them, for then the viewer is asked to compare quantities located in spatial disarray both within and between pies... Given their low data-density and failure to order numbers along a visual dimension, pie charts should never be used.

-Edward Tufte, The Visual Display of Quantitative Information


Who do you think did a better job in tonight's debate?

	Clinton	Trump
Among Democrats	99%	1%
Among Republicans	53%	47%




- Afghanistan
- Albania
- Algeria
- Angola
- Argentina
- Australia
- Austria
- Bahrain
- Bangladesh
- Belgium
- Benin
- Bolivia
- Bosnia and Herzegovina
- Botswana
- Brazil
- Bulgaria
- Burkina Faso
- Burundi
- Cambodia
- Cameroon


All good pie charts are jokes...




The most important measurement should exploit the highest ranked encoding possible.

- Position along a common scale
- Position on identical but nonaligned scales
- Length
- Angle or Slope
- Area
- Volume or Density or Color saturation/hue










The most important measurement should exploit the highest ranked encoding possible.


- Position along a common scale
- Position on identical but nonaligned scales
- Length
- Angle or Slope
- Area
- Volume or Density or Color saturation/hue









Observation: Comparison is trivial on a common scale.







Today's Learning Goals

- Appreciate the major elements of **exploratory data analysis** and why it is important to visualize data.
- Be conversant with **data visualization best practices** and understand how good visualizations optimize for the human visual system.
- Be able to generate informative graphical displays including **scatterplots, histograms, bar graphs, boxplots, dendrograms** and **heatmaps** and thereby gain exposure to the extensive graphical capabilities of R.
- Appreciate that you can build even more complex charts with **ggplot** and additional R packages such as **rgl**.

Do it Yourself!



Hands-on

Section 1 only please


Different graphs for different purposes

Exploratory graphs: many images for a narrow audience (you!)

Presentation graphs: single image for a large audience



Presentation



Exploration


Roles of graphics in data analysis

- Graphs (& tables) are forms of communication:
 - What is the audience?
 - What is the message?

Analysis graphs: design to see patterns, trends, aid the process of data description, interpretation


Presentation graphs: design to attract attention, make a point, illustrate a conclusion

Basic functions of data display




Core R Graph Types


Scatter plot




Bar Chart




Histogram




Boxplot




Dot Chart




Stripchart







Pie Chart




Smooth Scatter



Cluster Dendrogram




The R Painters Model




Side-Note: “Red and green should never be seen”

Core Graph Types


Scatter plot




Bar Chart




Histogram




Boxplot




Dot Chart




Stripchart



Pie Chart



Smooth Scatter




- Local options to change a specific plot
- Global options to affect all graphs

Common Options


- **Axis scales**
 - `xlim c(min,max)`
 - `ylim c(min,max)`
 - **Axis labels**
 - `xlab(text)`
 - `ylab(text)`
 - **Plot titles**
 - `main(text)`
 - `sub(text)`
 - **Plot characters**
 - `pch(number)`
 - `cex(number)`
-
- Local options to change a specific plot
 - Global options to affect all graphs

Plot Characters

cex sizes




Plot Characters



```
plot( 1:5, pch=1:5, cex=1:5 )
```


Plot Type Specific Options


Plot (scatterplots and line graphs)



- Input: Almost anything. 2 x Vectors
- Output: Nothing
- Options:
 - `type` `l`=line, `p`=point, `b`=line+point
 - `lwd` line width (thickness)
 - `lty` line type (1=solid,2=dashed,3=dotted etc.)

```
plot( c(1:10)^2, typ="b", lwd=4, lty=3 )
```


Barplot (bar graphs)



- **Input:** Vector (single) or Matrix (stack or group)
- **Output:** Bar centre positions
- **Options:**
 - `names.arg` Bar labels (if not from data)
 - `horiz=TRUE` Plot horizontally
 - `beside=TRUE` Plot multiple series as a group not stacked

```
barplot(VADeaths, beside = TRUE)
```

Hist (histograms)




- Input: Vector
- Output: Summary of binned data
- Options:
 - `breaks` Number or limits of bins
 - `probability` Y axis is probability, not freq
 - `labels` Per bin text labels

```
hist( c( rnorm(1000,0), rnorm(1000,4) ), breaks=20 )
```

Boxplot

Boxplot



- **Input:** Vector, List or formula (`data~factor`)
- **Output:** Summary of the boxplot parameters
- **Options:**
 - `range` Sensitivity of whiskers
 - `varwidth` Width represents total observations
 - `horizontal` Plot horizontally

```
boxplot( cbind( rnorm(1000,0), rnorm(1000,4) ) )
```

Controlling plot area options with `par`

Par

- The `par` function controls global parameters affecting all plots in the current plot area
- Changes affect all subsequent plots
- Many `par` options can also be passed to individual plots

?par

Par examples

- **Reading current value**
 - `par()$cex`
- **Setting a value**
 - `par(cex=1.5) -> old.par`
- **Restoring a value**
 - `par(old.par)`
 - `dev.off()`

Par options

- **Margins**


- `mai` (set margins in inches)
- `mar` (set margins in number of lines)
- `mex` (set lines per inch)
- 4 element vector (bottom, left, top, right)

- **Warning**


- `Error in plot.new() : figure margins too large`

```
par( mar=c(2, 10, 1, 1) )
```

mar=c(5,4,4,2)





mar=c(2,10,10,1)



Par options


- **Fonts and labels**
 - `cex` - **global char expansion**
 - `cex.axis`
 - `cex.lab`
 - `cex.main`
 - `cex.sub`



```
par( cex.main=1.5, cex.axis=0.5, cex.lab=2 )
```

Par options

- Multi-panel
 - `par(mfrow(rows, cols))`



```
par( mfrow(3, 4) )
```

Do it Yourself!

Hands-on

Section 2 only please

Using Color

Specifying colors

- **Hexadecimal strings**
 - `#FF0000` (red)
 - `#0000FF` (blue)
 - `#CC00CC` (purple)
- **Controlled names**
 - `"red"` `"green"` etc.
 - `colors()`

Built in color schemes

- Functions to generate colors
- Pass in number of colors to make
- Functions:
 - `rainbow()`
 - `heat.colors()`
 - `cm.colors()`
 - `terrain.colors()`
 - `topo.colors()`

`rainbow(7)`

Rainbow Colours



Heat Colours



CM Colours



Terrain Colours



Topo Colours



`rainbow(7)`

Color Packages

- **Color Brewer**
 - Set of pre-defined, optimized palettes
 - `library(RColorBrewer)`
 - `brewer.pal(n_colours, palette)`
- **ColorRamps**
 - Create smooth palettes for ramped color
 - Generates a function to make actual color vectors
 - `colorRampPalette(c("red", "white", "blue"))`
 - `colorRampPalette(c("red", "white", "blue"))(5)`

Applying Color to Plots

- Vector of numbers or specified colors passed to the `col` parameter of a plot function
- Vector of **factors** used to divide the data
 - Colors will be taken from the set color **palette**
 - Can read or set using **palette** function
 - `palette()`
 - `palette(brewer.pal(9, "Set1"))`

```
plot( 1:5, col=1:5, pch=15, cex=2)
```

Dynamic use of color

- Coloring by density
 - Pass data and palette to `densCols()`
 - Vector of colors returned
- Coloring by value
 - Need function to map values to colors

Do it Yourself!

Hands-on

Section 3 only please

For next day:

Section 4 Revisited

- Open your previous Lecture5 RStudio **project** (and your saved **R script**)
- Locate and open in RStudio the downloaded file `color_to_value_map.r`
- This is an example of a poorly written function typical of something you might get from a lab mate that knows some R...

(POOR!) Color Mapping Function

```
map.colors <- function (value,high.low,palette) {  
  proportion <- ((value-high.low[1]) / (high.low[2]-high.low[1]))  
  index <- round ((length(palette)-1)*proportion)+1  
  return (palette[index])  
}
```

Talking point:

- Can you figure out what this function it is supposed to do?
- What format should the inputs be in order to work?
- How could we improve this function?

Homework!

New DataCamp Assignments

- Introduction to R Markdown
- Functions
- Loops

[Muddy Point Assessment Form Link](#)